



### Description

It is a one-component acrylic resin-based coating, slip-resistant, designed for outdoor surfaces.

### Application

- Is employed in the bonding of rubber panels, PVC, EPDM, homogeneous and heterogeneous vinyl sheets, and PU foam.
- Applied only on dry surfaces, protected from arising humidity and free of materials that might prevent bonding.
- It creates colorful outdoor floors that are easy to clean.
- It enhances the durability of both new and old floors alike.
- It preserves the floors, enhances their hardness, and deeply penetrates them.

### Technical Data

Test	Result
Appearance	One-component acrylic resin
Colors	Light beige
Density (Kg/m <sup>3</sup> )	1.6 - 1.7
Viscosity (cps)	1000 – 3500 mPa.s at 25°C
Walkability	after 1 day
Temperature for the application and drying of the material	35°C

### Packaging

Supplied in 75 kg drum packages

### Storage

12 months in unopened containers in dry places with minimum temperature 5°C and maximum temperature 30 °C

### Consumption

200-400 gr/m<sup>2</sup> depending on the type, roughness and absorbency of the underlay

### Application Instructions

#### Substrate

The level, dry, clean, and free of cracks, undulations, and dust solid substrates must have in order to ensure proper adhesion. On dry surfaces without rising humidity issues

#### Preparation Work

Before beginning installation, the substrate's surface needs to be thoroughly cleaned with a brush. Before beginning installation, minor inclinations must be leveled.

### Application

- Surface priming to ensure appropriate subfloor adherence.
- Saturating the surface with one or more layers of application. Prevent the accumulation of the substance in puddles.
- it is a viscous off-white colored paste supplied in plastic drum.
- Mix thoroughly until a uniform consistency is obtained throughout. A drill with paddle attachment should be used to ensure complete mixing. Scrape the sides thoroughly during this process. Care should be taken to avoid spillage when mixing.
- Using a toothed spatula, apply and spread evenly after stirring before use.
- Give the product five to fifteen minutes to cure before installing the floor covering. (based on substrate, temperature, and tool).
- It is essential to ensure good contact between the floor covering and the adhesive.
- Clean any excess of adhesive using water immediately.
- Avoid letting the adhesive dry completely as this will prevent covering laying from occurring.
- After the substance has been spread, be sure to avoid any holes. Depending on the kind, level of absorption, and roughness of the underlay, consumption ranges from 200 to 400 gr/m<sup>2</sup>.

### Cleaning

Tools should be cleaned with water immediately after use

### Health and Safety

- The application must take place in well-aired places using protective gloves
- Skin or eye contact must be avoided, otherwise wash carefully with soap and water.
- Do not dispose directly to water or soil. Burry in landfill in accordance with the local regulations.
- For further information, request material safety data sheet (MSDS) for the product