



HOPPEC RUBBER STARIS

Description

It consists of fine-grained recycled tire rubber (SBR – SBR Mix EPDM) bonded with polyurethane elastomer.
Color(s): Multi colors (available on request).

Product testing

Test	Result
Tensile strength	Approx. 0.7 N/mm ²
Elongation at break	Approx. 70%
Hardness	60 ± 5 Shore A
Fire resistance class	Efl
Abrasion Resistance	rV5.9
Resistance to Chemicals	Resistance to weak Acids and Oils
UV	Good Resistance

Dimensions

Thickness(es)	60mm (customizable)
Length x width	500 * 350 mm

Application

Rubber tiles are versatile and widely used across various industries and settings due to their durability, safety features, and ease of maintenance. Typical applications include:

- indoor and outdoor staircases in commercial and residential buildings.
- Public facilities such as schools, hospitals, and offices.
- Transportation Vehicles
- Used as a cover for the solid ladder, concrete, and wood stairs

Advantages

High Slip Resistance: Textured or ribbed surface for enhanced safety.

- Durable & Long-Lasting: Made from high-quality rubber (EPDM/SBR) for heavy use.
- Shock Absorption: Reduces impact and vibrations for comfort.
- Water & Moisture Resistant: Ideal for indoor and outdoor applications.
- Easy Installation & Maintenance: Simple to install and clean.
- Sound Insulation: Minimizes noise from foot traffic.
- Fire & Heat Resistant: Ensures safety and longevity.
- Variety of Colors & Designs: Matches different environments and aesthetics.