

Technical data sheet

HOPPEC RUBBER SBR GRANULES

Description

Finely ground black or multicolored rubber that has been salvaged from brand-new, pre-consumer post-industrial scrap rubber and chopped and classed to fit inside each precise size parameter. Because to its improved polymer quality, our premium granule lasts longer under UV situations.

Product testing

Test	Result
Appearance	Black or Colored Granules
Density	1.10 - 1.20
Hardness (Shore A)	60 – 90
Tensile Strength	3000 psi
Granules size	0.5 – 1.5 mm
	1.5 – 4 mm

Storage

Keep material dry at all times and out of direct UV contact while in the plastic packaging

Packaging

• Available in bulk bags or 40kg plastic bag.

Consumption

0.45 g/cm3

Characteristics

- Clear of contaminants such as metal, stone, fiber, and others.
- Less than 2% dust content
- Standards for sieve analysis are available upon request.

Application

Used in applications like playground wearing courses, shock pads and E-layers, turf infill, and synthetic running tracks. With the necessary machinery and an authorized binder, this material can be spread or paved.

Health and Safety

- non-toxic, non-corrosive, and non-dangerous.
- Do not dispose directly to water or soil. Burry in landfill in accordance with the local regulations.
- For further information, request material safety data sheet (MSDS) for the product.