



## HOPPEC RUBBER BORDERS

### Description

It consists of fine grained recycled tire rubber ( SBR - SBR Mix EPDM ) bonded with polyurethane elastomer. Color(s): Multi colors ( available on request )

### Product testing

Test	Result
Tensile strength	Approx. 12.0 N/mm <sup>2</sup>
Elongation at break	Approx. 325%
Hardness	75 ± 5 Shore A
Fire resistance class	EF1
Abrasion Resistance	rV5.9
Resistance to Chemicals	Resistance to weak Acids and Oils
UV	Good Resistance

### Dimensions

Thickness(es)	20-50 mm (customizable)
Length x width	1000 * 100 *100 mm

### Application

Rubber tiles are versatile and widely used across various industries and settings due to their durability, safety features, and ease of maintenance. Typical applications include:

- indoor and outdoor staircases in commercial and residential buildings.
- Public facilities such as schools, hospitals, and offices.
- Sports Facilities and Gyms.
- Ramps and Entryways
- Interior Design and Finishing

### Advantages

High Slip Resistance: Textured or ribbed surface for enhanced safety.

- Durable & Long-Lasting: Made from high-quality rubber (EPDM/SBR) for heavy use.
- Shock Absorption: Reduces impact and vibrations for comfort.
- Water & Moisture Resistant: Ideal for indoor and outdoor applications.
- Easy Installation & Maintenance: Simple to install and clean.
- Sound Insulation: Minimizes noise from foot traffic.
- Fire & Heat Resistant: Ensures safety and longevity.
- Variety of Colors & Designs: Matches different environments and aesthetics.