



## HOPPEC RUBBER Corners

### Description

It consists of fine-grained recycled tire rubber (SBR- SBR Mix EPDM) bonded with polyurethane elastomer.  
Color(s): Multi colors (available on request).

### Product testing

Test	Result
Tensile strength	Approx. 0.7 N/mm <sup>2</sup>
Elongation at break	Approx. 70%
Hardness	60 ± 5 Shore A
Fire resistance class	ER
Abrasion Resistance	rV5.9
Resistance to Chemicals	Resistance to weak Acids and Oils
UV	Good Resistance

### Dimensions

Thickness(es)	20mm (customizable)
Length x width	1000 * 90 * 90 mm

### Application

Rubber tiles are versatile and widely used across various industries and settings due to their durability, safety features, and ease of maintenance. Typical applications include:

- indoor and outdoor staircases in commercial and residential buildings.
- Public facilities such as schools, hospitals, and offices.
- Sports Facilities
- In parking lots and garages
- In elevators

### Advantages

High Slip Resistance: Textured or ribbed surface for enhanced safety.

- Durable & Long-Lasting: Made from high-quality rubber (EPDM/SBR) for heavy use.
- Shock Absorption: Reduces impact and vibrations for comfort.
- Water & Moisture Resistant: Ideal for indoor and outdoor applications.
- Easy Installation & Maintenance: Simple to install and clean.
- Sound Insulation: Minimizes noise from foot traffic.
- Fire & Heat Resistant: Ensures safety and longevity.
- Variety of Colors & Designs: Matches different environments and aesthetics.